

# SP-Series

## Lighted Panels



Audio/Visual Devices

### General

The SP-2/MNS features typical mass notification messages in an exit-sign style enclosure. The slim 2½" (6.4 cm) deep box is made of steel, is painted white and is designed for surface mounting. The messages are printed in clear within a black box on clear film. The red and green colors are printed on another sheet behind the words. Both sheets slide into the enclosure and are secured by a removable side-access panel. The messages will remain hidden (black) until the light source is activated.

The active message is indicated by illuminating the words from behind using LED light bars of the required color. This low current, long-life light source provides years of dependable service. The SP-2/MNS operates at 24 VDC - 120 ma. - maximum.

The standard SP-2/MNS model features two messages: "ANNOUNCEMENT" and "EVACUATE" as shown. The SP-4 features four messages: "FIRE", "WEATHER", "ANNOUNCEMENT" and "EVACUATE".

### Features

- Made in the USA.
- Slim design.
- Sturdy metal enclosure.
- Easy access for wiring.
- Size: 7½" H x 12" W x 2½" D  
(19.1cmH x 30.5 cmW x 6.4 cmD).
- Letter height is 3" (216pt).

### Ordering Information

**SP-2/MNS:** Two message sign, "ANNOUNCEMENT" and "EVACUATE".

**SP-4:** Four message sign, "FIRE", "WEATHER", "ANNOUNCEMENT", and "EVACUATE".



Shown Activated

---

©2008 by Honeywell International Inc. All rights reserved. Unauthorized use of this document is strictly prohibited.



This document is not intended to be used for installation purposes.  
We try to keep our product information up-to-date and accurate.  
We cannot cover all specific applications or anticipate all requirements.  
All specifications are subject to change without notice.

For more information, contact Notifier. Phone: (203) 484-7161, FAX: (203) 484-7118.  
[www.notifier.com](http://www.notifier.com)

## SP-Series

### Lighted Panels



Audio/Visual Devices

#### General

The SP-2/MNS features typical mass notification messages in an exit-sign style enclosure. The slim 2½" (6.4 cm) deep box is made of steel, is painted white and is designed for surface mounting. The messages are printed in clear within a black box on clear film. The red and green colors are printed on another sheet behind the words. Both sheets slide into the enclosure and are secured by a removable side-access panel. The messages will remain hidden (black) until the light source is activated.

The active message is indicated by illuminating the words from behind using LED light bars of the required color. This low current, long-life light source provides years of dependable service. The SP-2/MNS operates at 24 VDC - 120 ma. - maximum.

The standard SP-2/MNS model features two messages: "ANNOUNCEMENT" and "EVACUATE" as shown. The SP-4 features four messages: "FIRE", "WEATHER", "ANNOUNCEMENT" and "EVACUATE".

#### Features

- Made in the USA.
- Slim design.
- Sturdy metal enclosure.
- Easy access for wiring.
- Size: 7½" H x 12" W x 2½" D  
(19.1cmH x 30.5 cmW x 6.4 cmD).
- Letter height is 3" (216pt).

#### Ordering Information

**SP-2/MNS:** Two message sign, "ANNOUNCEMENT" and "EVACUATE".

**SP-4:** Four message sign, "FIRE", "WEATHER", "ANNOUNCEMENT", and "EVACUATE".



Shown Activated

---

©2008 by Honeywell International Inc. All rights reserved. Unauthorized use of this document is strictly prohibited.



This document is not intended to be used for installation purposes.  
We try to keep our product information up-to-date and accurate.  
We cannot cover all specific applications or anticipate all requirements.  
All specifications are subject to change without notice.

For more information, contact Notifier. Phone: (203) 484-7161, FAX: (203) 484-7118.  
[www.notifier.com](http://www.notifier.com)

## SP-Series

### Lighted Panels



Audio/Visual Devices

#### General

The SP-2/MNS features typical mass notification messages in an exit-sign style enclosure. The slim 2½" (6.4 cm) deep box is made of steel, is painted white and is designed for surface mounting. The messages are printed in clear within a black box on clear film. The red and green colors are printed on another sheet behind the words. Both sheets slide into the enclosure and are secured by a removable side-access panel. The messages will remain hidden (black) until the light source is activated.

The active message is indicated by illuminating the words from behind using LED light bars of the required color. This low current, long-life light source provides years of dependable service. The SP-2/MNS operates at 24 VDC - 120 ma. - maximum.

The standard SP-2/MNS model features two messages: "ANNOUNCEMENT" and "EVACUATE" as shown. The SP-4 features four messages: "FIRE", "WEATHER", "ANNOUNCEMENT" and "EVACUATE".

#### Features

- Made in the USA.
- Slim design.
- Sturdy metal enclosure.
- Easy access for wiring.
- Size: 7½" H x 12" W x 2½" D  
(19.1cmH x 30.5 cmW x 6.4 cmD).
- Letter height is 3" (216pt).

#### Ordering Information

**SP-2/MNS:** Two message sign, "ANNOUNCEMENT" and "EVACUATE".

**SP-4:** Four message sign, "FIRE", "WEATHER", "ANNOUNCEMENT", and "EVACUATE".



Shown Activated

---

©2008 by Honeywell International Inc. All rights reserved. Unauthorized use of this document is strictly prohibited.



This document is not intended to be used for installation purposes.  
We try to keep our product information up-to-date and accurate.  
We cannot cover all specific applications or anticipate all requirements.  
All specifications are subject to change without notice.

For more information, contact Notifier. Phone: (203) 484-7161, FAX: (203) 484-7118.  
[www.notifier.com](http://www.notifier.com)

## SP-Series

### Lighted Panels



Audio/Visual Devices

#### General

The SP-2/MNS features typical mass notification messages in an exit-sign style enclosure. The slim 2½" (6.4 cm) deep box is made of steel, is painted white and is designed for surface mounting. The messages are printed in clear within a black box on clear film. The red and green colors are printed on another sheet behind the words. Both sheets slide into the enclosure and are secured by a removable side-access panel. The messages will remain hidden (black) until the light source is activated.

The active message is indicated by illuminating the words from behind using LED light bars of the required color. This low current, long-life light source provides years of dependable service. The SP-2/MNS operates at 24 VDC - 120 ma. - maximum.

The standard SP-2/MNS model features two messages: "ANNOUNCEMENT" and "EVACUATE" as shown. The SP-4 features four messages: "FIRE", "WEATHER", "ANNOUNCEMENT" and "EVACUATE".

#### Features

- Made in the USA.
- Slim design.
- Sturdy metal enclosure.
- Easy access for wiring.
- Size: 7½" H x 12" W x 2½" D  
(19.1cmH x 30.5 cmW x 6.4 cmD).
- Letter height is 3" (216pt).

#### Ordering Information

**SP-2/MNS:** Two message sign, "ANNOUNCEMENT" and "EVACUATE".

**SP-4:** Four message sign, "FIRE", "WEATHER", "ANNOUNCEMENT", and "EVACUATE".



Shown Activated

---

©2008 by Honeywell International Inc. All rights reserved. Unauthorized use of this document is strictly prohibited.



This document is not intended to be used for installation purposes.  
We try to keep our product information up-to-date and accurate.  
We cannot cover all specific applications or anticipate all requirements.  
All specifications are subject to change without notice.

For more information, contact Notifier. Phone: (203) 484-7161, FAX: (203) 484-7118.  
[www.notifier.com](http://www.notifier.com)